

LV HRC fuse link, NH1, In: 160 A, gG, Un AC: 500 V, Un DC: 440 V,
Combination indicator, non-insulated grip lugs

Model	
Product designation	LV HRC fuse link
Design of an identification indicator	Combination alarms

General technical data	
Size of fuse system / acc. to DIN EN 60269-1	NH1
Operating class of the fuse link	gG
Supply voltage	
• at AC / rated value	500 V
• at DC	440 V

Electricity	
Current / at AC / rated value	160 A

Certificates	
Shipping Approval	other

[sonstig](#)



GL

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3NA7136-0RC>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3NA7136-0RC/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NA7136-0RC

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>