

Withdrawable coil for size S6 for contactors 3RT105 / 3RT145
 AC/DC operation 23 ... 26 V UC, Drive: conventional screw terminal



Figure similar

| General technical data | |
|--|------------------------------|
| Product brand name | SIRIUS |
| Product designation | Magnet coil |
| Control circuit | |
| Type of voltage of the control supply voltage | AC/DC |
| Control supply voltage | |
| <ul style="list-style-type: none"> • 1 at AC <ul style="list-style-type: none"> — at 50 Hz rated value — at 60 Hz rated value • 2 at AC <ul style="list-style-type: none"> — at 50 Hz rated value — at 60 Hz rated value | 23 V 23 V 26 V 26 V |
| Control supply voltage | |
| <ul style="list-style-type: none"> • 1 at DC rated value • 2 at DC rated value | 23 V 26 V |
| Certificates/approvals | |

| General Product Approval | Functional Safety/Safety of Machinery | Declaration of Conformity | Test Certificates |
|--------------------------|---------------------------------------|---------------------------|-------------------|
|--------------------------|---------------------------------------|---------------------------|-------------------|



[Type Examination Certificate](#)



[Special Test Certificate](#)

Shipping Approval



other

[Confirmation](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT1955-5AB31>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT1955-5AB31>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT1955-5AB31>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT1955-5AB31&lang=en

last modified:

07/25/2018